



PLANET 200 TSH

POWER MAX

4700
W

WATER LIFT

3260
mmH₂O

AIR FLOW

465 m³/h

TANK CAPACITY

100 l

CARATTERISTICHE ESCLUSIVE

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ H CERTIFICATION
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ TANGENTIAL OR METAL INLET
- ▶ BIG AND BRAKED WHEELS
- ▶ VISUAL FILLING INDICATOR
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ FILTER OVERPRESSURE INDICATORS
- ▶ SAFETY DISPOSAL SYSTEMS
- ▶ RESISTANT FRAMEWORK AND INLET PLUG FOR SAFE TRANSFER



SETTORI DI UTILIZZO

PHARMA INDUSTRY



AGRICULTURE



CONSTRUCTION



INDUSTRY



LOGISTIC & TRANSPORT



SPECS



SAFETY DISPOSAL SYSTEMS



RESISTANT FRAMEWORK AND INLET PLUG FOR SAFE TRANSFER



H13 CARTRIDGE

DATI TECNICI

		PLANET 200 TSH
Codice		ASID00398
TECHNICAL DATA		
Usage		DRY
Number of phases		monofase
Voltage	V	220-240
Frequency	Hz	50-60
Motor		3
Power	W	4000-4700 max
Water lift	mmH2O	3260
Air flow	m³/h	465
Tank capacity	l	100
Diameter of inlet	mm	70
Filtering surface	cm²	36.200
Sound Pressure Level	dB(A)	76
Dimensions (LxWxH)	mm	660x990x1630
Weight	Kg	70

STANDARD EQUIPMENT

CODICE: FTDP00587
HEPA CARTRIDGE H13
36200 cm²



CODICE: FTDP40014
POLYCARBON PREFILTER



CODICE: PMVR06188
COMPLETE CAP FOR INLET
(FOR SAFE DISPOSAL)



CODICE: IMBA00364
PAPER TANK KIT FOR
TOXIC SUBSTANCES



OPTIONAL ACCESSORIES

PMDT00444 - BASIC TOOL KIT Ø50-70 MM COMPOSED OF:

CODICE: TBFX49497
FLEXIBLE HOSE Ø50-70
mm WITH CUFFS 3 m



CODICE: LAFN49581
COMPLETE ALUMINIUM
DOUBLE WAND Ø50 mm



CODICE: SPPV01960
BRISTLE BRUSH Ø50 mm



CODICE: SPPV49600
CHROMED FLAT LANCE
Ø50 mm



CODICE: MPVR40232
SQUEEGEE X2 PCS
Ø50 mm



PMDT00426 - ANTI-STATIC TOOL KIT Ø50-70 MM COMPOSED OF:

CODICE: TBFX00922
CONDUCTIVE FLEXIBLE
HOSE Ø50-70 mm WITH
CUFFS 3 m



CODICE: LAFN49581
COMPLETE ALUMINIUM
DOUBLE WAND Ø50 mm



CODICE: SPPV01960
BRISTLE BRUSH Ø50 mm



CODICE: SPPV49597
RUBBER FLAT LANCE
Ø50 mm

